


2213 Colorado Classic



100% BCF Perpetual™ Contract

- Engineered with a higher dpf
- Solution dyed for rich color and easy to clean
- Durable, resilient, and strong
- Twisted and heat-set for lasting beauty



Stain Proof – No Exceptions™

Spills won't bond with Perpetual carpet fiber, so they can always be removed. Perpetual™ carpet is covered by our lifetime Stain Proof – No Exceptions™ warranty. This means your carpet is going to stay beautiful in spite of life's little mishaps. Liquid spills 'bead up' so that you can remove them easily. Most spots can be completely removed by simply blotting the spill. So the beautiful color of your carpet will go on in perpetuity.




Scoured & Extracted™ to Stay Clean Longer

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



BioFresh™ Anti-microbial

This carpet incorporates BioFresh™ anti-microbial treatment to inhibit the growth of bacteria, fungi and mildew, ensuring lasting hygienic freshness. Carpets with BioFresh™ are ideal for areas where spills and soil could promote bacterial growth.



Lifetime Warranties

- Commercial wear
- Stain Proof – No Exceptions™
- AccuPattern™
- Colorfast
- Anti-shock

See full text for details.

Style 2213

01 Galvanized	02 Woodcliff	06 Cinderblock	07 Beach Gold
08 Mai Tai	11 Passage	12 Wicker Mat	13 Aspen Sky
17 Red Coral	21 Blue Reef	27 Taproom	37 Night Rider

Style 2213 Colorado Classic
Manufacturer Kraus®

CONSTRUCTION

Fiber system	100% BCF Perpetual™ Contract	
Construction	Textured cut/loop pattern	
Standard backing system	Dual bonded woven synthetic	
Pile weight	30 oz./y ²	1017 g/m ²
Pile height	0.12"/0.28"	3 mm/7 mm
Gauge	1/10	39.4 rows/10 cm
Stitches	13.2 s.p.i.	52.0 stitches/10 cm
Density	5500	15.4 kilotex/cm ²

PROTECTION

Coloration	Solution dyed
Stain resistance	8.0 (AATCC 175) minimum
Soil protection	Scoured & Extracted™ PermaSeal™ protected
Anti-microbial protection	BioFresh™ present in backing laminate

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus
Environmental awareness	Eligible for any recycling program

PERFORMANCE

Static generation	3.0 kV or less (AATCC 134)
Flammability	CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement) Radiant Panel ASTM E648 – Class I
Anti-microbial performance	Contact inhibition of fungal and bacterial growth tested according to AATCC methods 30 & 147
Colorfastness to light	5.0 (AATCC 16)

INSTALLATION

Format	12' wide	3.66 m
Approximate pattern repeat (w x l)	12" x 8 ½"	30.5 cm x 21.6 cm
Recommended adhesive	Kraus Premium Adhesive™ KPA-302	
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Mandatory for cushion installation	

WARRANTIES

Lifetime Warranties (see full text for details)	Commercial wear Stain Proof – No Exceptions™ AccuPattern™ Colorfast Anti-shock
--	--

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. Shading is a characteristic of a cut pile carpet and not a manufacturing defect. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. *Percentages of recycled content are accurate at date of printing. The availability of these inputs could fluctuate over time. See krausflooring.com for latest specifications.

E&OE.