



2094 Bridge the Gap



Stain Proof – No Exceptions™

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain Proof – No Exceptions™ warranty. Most spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.



Wear

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.



Anti-shock


This carpet features permanently conductive fibers and will not generate a static shock exceeding industry standard at a relative humidity of 20% and a room temperature of 21°C.



PermaSeal™: More Spill Protection

In a heat-applied process, the fibers are encapsulated with PermaSeal™ protectant. PermaSeal™ carpets look better longer because:

- Spills can be spot cleaned more easily
- Dirt Vacuums away more easily



Lifetime Warranties

- Commercial Wear
- Stain Proof – No Exceptions™
- AccuPattern™
- Anti-shock

Style 2094

09 Golden Gate	16 Cinderblock	17 Cork	24 Iced Coffee
28 Soft Copper	29 Thyme	32 Patch of Blue	35 Onyx
37 Shamrock	39 Mineral	40 Chrome	42 Gunmetal
43 Cactus	44 Pan Am	46 Purple Haze	48 Sand Bluff

Style 2094 Bridge the Gap
Manufacturer Kraus®

CONSTRUCTION

Fiber system	100% BCF Ultrrel:indelible™ nylon	
Construction	Pattern scroll loop	
Standard backing system	Dual bonded woven synthetic	
Pile weight	28 oz./y ²	950 g/m ²
Pile height	0.16"/0.12"	4 mm/3 mm
Gauge	1/12	31.5 rows/10 cm
Stitches	14.6 s.p.i.	57.5 stitches/10 cm
Density	8400	14.0 kilotex/cm ²

PROTECTION

Coloration	100% Solution dyed	
Stain resistance	8.0 (AATCC 175) minimum	
Soil protection	Scoured & Extracted™ PermaSeal™ protected	
Anti-microbial protection	BioFresh™ present in backing laminate	

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus
Environmental awareness	Eligible for any recycling program

PERFORMANCE

Static generation	3.0 kV or less (AATCC 134)
Flammability	CGSB 4GP-129 Radiant Panel ASTM E648 – Class I
Anti-microbial performance	Contact inhibition of fungal and bacterial growth tested according to AATCC methods 30 & 147
Colourfastness to light	5.0 (AATCC 16)

INSTALLATION

Format	12' wide	3.66 m
Approximate pattern repeat (w x l)	24" x 31"	61 cm x 78 cm
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installations	

WARRANTIES

Lifetime Warranties (see full text for details)	Commercial Wear Stain Proof – No Exceptions™ AccuPattern™ Anti-shock
--	---

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. *Percentages of recycled content and wind power are accurate at date of printing. The availability of these inputs could fluctuate over time. See krausflooring.com for latest specifications.

E&OE.