


2179 Distinctive ZL




Zipperlock® Technology

Yarn that is regularly found in loop pile carpet is tufted with a straight stitch that may unravel and fray over time. Our Zipperlock® technology allows our carpets to be tufted with an interlocking stitch to prevent unraveling providing the long lasting beauty of your carpet.



Stain Proof – No Exceptions™

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain Proof – No Exceptions™ warranty. Most spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.




Wear

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.



Anti-shock

This carpet features permanently conductive fibers and will not generate a static shock exceeding industry standard at a relative humidity of 20% and a room temperature of 21°C.



Commercial Warranties

- Lifetime Stain Proof – No Exceptions™
- 10 year Commercial Wear
- 10 year ZipperLock® + no edge ravel + no delamination
- 10 year AccuPattern™
- 10 year Anti-shock

Style 2179

01 Cashew
28 Russet

02 Tawny Taupe
65 Rocky Coast

04 Nut Brown
67 Nightfall

22 Spanish Brown
71 Coal

Style 2179 Distinctive ZL
Manufacturer Kraus®

CONSTRUCTION

Fiber system	100% BCF Strudon®	
Construction	Patterned multi-level loop	
Standard backing system	ZipperLock® dual bonding	
Pile weight	24 oz./y ²	814 g/m ²
Pile height	0.24"/0.12"	6 mm/3 mm
Gauge	1/12	47.3 rows/10 cm
Stitches	9.0 s.p.i.	35.4 stitches/10 cm
Density	6200	12.1 kilotex/cm ²

PROTECTION

Coloration	Solution dyed
Stain resistance	Stain Proof – No Exceptions™
Stain/soil protection	Scoured & Extracted™

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 4678
Environmental awareness	Eligible for any recycling program	

PERFORMANCE

Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols	
Static generation	3.0 kV or less (AATCC 134)	
Flammability	CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement) Radiant Panel ASTM E648 – Class II	
Colorfastness to light	5.0 (AATCC 16)	

INSTALLATION

Format	12' wide	3.66 m
Approximate pattern repeat (w x l)	24" x 21"	61 cm x 53 cm
Recommended adhesive	Kraus I Premium Adhesive™ KPA-302	
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installations	

WARRANTIES

Warranties	Lifetime Stain Proof – No Exceptions™	
(See full text for details)	10 year Commercial Wear	
	10 year ZipperLock® + no edge ravel + no delamination	
	10 year AccuPattern™	
	10 year Anti-shock	

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. For best results, seams must be row cut and the carpet must be dry laid to optimize pattern match. Due to dye lot variations, actual material may vary slightly from samples. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. See krausflooring.com for latest specifications.

E&OE.