



2243

MANDATE

elite



Stain Proof – No Exceptions™

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain Proof – No Exceptions warranty. Most spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.



Wear

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.



Zipperlock® Technology

Yarn that is regularly found in loop pile carpet is tufted with a straight stitch that may unravel and fray over time. Our Zipperlock technology allows our carpets to be tufted with an interlocking stitch to prevent unraveling providing the long lasting beauty of your carpet.



Lifetime Warranty

- Stain Proof – No Exceptions™
- Zipperlock® + no edge ravel + no delamination
- Commercial Wear
- Colorfast
- Anti-shock



22 | Sanction Silver



10 | Ruling Range



09 | Ecrú Edict



01 | Action Agate



14 | Command Cove



23 | Peppery Power



12 | Dusk Decree



13 | Outback Order



20 | Authorize Auburn



16 | Chestnut Charge



03 | Fiat Fire



33 | Instruct Inlet

specifications

Fiber system	100% BCF Ultrel Plus nylon	
Construction	Level loop	
Backing system	ZipperLock® dual bonded woven synthetic	
Pile weight	24 oz./y ²	882 g/m ²
Pile height	0.12"	3.5 mm
Gauge	1/10	39.4 rows/10 cm
Stitches	9.2 s.p.i.	36.2 stitches/10 cm
Density	7900	20.1 kilotex/cm ²
Coloration	100% Solution dyed	
Stain resistance	8.0 (AATCC 175) minimum	
Anti-microbial protection	BioFresh™ present in backing laminate	
CRI/CCI air quality test	Green Label Plus	GLP 1480
Environmental awareness	Eligible for any recycling program	
Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols	
Static generation	3.0kV or less (AATCC 134)	
Flammability	CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement) Radiant Panel ASTM E648 – Class I	
Anti-microbial performance	Contact inhibition of fungal and bacterial growth tested according to AATCC methods 30 & 147	
Colorfastness to light	5.0 (AATCC 16)	
Format	12' wide	3.66 m
Approximate pattern repeat (w x l)	Random	
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installations	
Lifetime warranties (See full text for details)	Stain Proof – No Exceptions™ ZipperLock® + no edge ravel + no delamination Commercial Wear Colorfast Anti-shock	

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. See krausflooring.com for latest specifications.

E&OE.

1404